



# SOLAR INVERTER



**Axpert Ultra 8 kW**

**Axpert Ultra 11 kW**

- Dual inputs and dual outputs for smart energy management
- Built-in 2.8" colored LCD with power lighting indicators
- Built-in WiFi with APP for mobile monitoring and OTA firmware upgrade
- Supports USB On-the-Go function
- Built-in BMS communication port
- External CT sensor to guarantee 100% self-consumption
- Built-in meter calibration for optimized system operation
- Support external BTS (Battery Temperature Sensor) detection
- Support optional GFCI, Rapid shutdown, AFCI detections
- Built-in anti-dust kit
- Parallel operation with 6 units

MODEL	Axpert Ultra 8K	Axpert Ultra 11K
<b>RATED POWER</b>	8000VA/8000W	11000VA/11000W
<b>PARALLEL CAPABILITY</b>	YES, 6 units	
<b>INPUT</b>		
Voltage	230 VAC	
Selectable Voltage Range	170-280 VAC (For Personal Computers) 90-280 VAC (For Home Appliances)	
Frequency Range	50 Hz/60 Hz (Auto sensing)	
<b>OUTPUT</b>		
AC Voltage Regulation (Batt. Mode)	230VAC ± 5%	
Surge Power	16000VA	22000VA
Efficiency (Peak)	93%	
Transfer Time	10 ms (For Personal Computers) ; 20 ms (For Home Appliances)	
Waveform	Pure sine wave	
<b>BATTERY</b>		
Battery Voltage	48 VDC	
Floating Charge Voltage	54 VDC	
Overcharge Protection	63 VDC	
<b>SOLAR CHARGER &amp; AC CHARGER</b>		
Solar Charger Type	MPPT	
Maximum PV Array Power	12000W (6000W x 2)	13000W (6500W x 2)
MPPT Range @ Operating Voltage	90 ~ 450 VDC	
Maximum PV Array Open Circuit Voltage	500 VDC	
Maximum PV Input Current	27A x 2 (MAX 40A)	
Maximum Solar Charge Current	150A	150A
Maximum AC Charge Current	120A	150A
Maximum Charge Current	150A	150A
<b>PHYSICAL</b>		
Dimension, D x W x H (mm)	145 x 438 x 553.6	
Net Weight (kgs)	18.4	
Communication Interface	USB/RS232/RS485/WiFi/Dry-contact/BTS Support optional GFCI, Rapid shutdown, AFCI detection	
External Current Sensor Port	Yes, built-in current transformer sensor	
<b>OPERATING ENVIRONMENT</b>		
Humidity	5% to 95% Relative Humidity(Non-condensing)	
Operating Temperature	-10°C to 50°C	
Storage Temperature	-15°C to 60°C	
<b>STANDARD</b>		
Compliance Safety	CE	

Product specifications are subject to change without further notice.